


the most vulnerable part of a vehicle - the chassis. Objects may vary from explosives, deases, the smuggling of human beings across borders or out of prison compounds. The verify from multiple angles, a suspicious threat before actually having to physically reach the subject. In the case of bomb squad technicians, being able to examine the object from a distance, before having to physically deal with it, could make the difference between life and death, as well as sparing the inconvenience of false alarms. All data from the system can be recorded to the local DVR system for training and investigation uses. The data can be tied to a LPR system for better documentation.

Secure Access

TI-2000-SM/TI-2500-S/TI-4000-S







- Capability to scan the vehicle while stationary.
- View above strut bars and other vehicle components from multiple angles and magnification.
- Live color video feed for constant eye contact with suspicious objects until threat confronted.
- System automatically scans chassis, using pre-programmed sequences or by user defined programs.
- 4 axis optical head unit.
- Manual mode for suspicious objects.
- Optional recording for training, investigation and documentation.
- The operator may be as far as 1500 meters from subject.
- Operator, Bomb squad technician may inspect objects from multiple angles before confronting them.
- Easy to use, only 20 minute training needed.
- Simple no use of computers.
- Quick installation.

APPLICATION

Government Offices, Embassies, Oil and Gas Refineries/Storage Depots, Border Checkpoints, Correctional Facilities, Power Plants, Sporting Events, Conventions and other sensitive sites.

SPECIFICATIONS

Dimensions:

- TI-2500-S: 2ft.3in. x 8ft.2in.x 7 ⁷/8 in. (70 x 250 x 20 cm)
- TI-4000-S: 2ft.3in. x 13ft. x $7^{7}/8$ in. (70 x 400 x 20 cm)
- TI-2000-SM: 6ft.2in. x 19ft.8in. x 7 ⁷/8 in. (190 x 600 x 20 cm) Including ramps (the TI-2500-S unit is planted in the ramp system). This mobile system comes on a trailer and includes a generator making it fully functional without any external needs.

Camera:

- High resolution color camera
- 440,000 pixels, 530 TV lines
- 36x optical auto focus zoom lens
- Wide dynamic range feature
- Work temperature range: -15°c + 60°c
- Monitor: 17" LCD
- Auto scanning sequence controls: Pan, Tilt, Zoom and Conveyer.



SAFEGUARDS

ph 201.488.1022 • fx 201.488.1244

75 ATLANTIC STREET HACKENSACK, NJ 07601

www.safeguards.com info@safeguards.com